



**HYDRA S**

# **HS-ULTRA SEALER**

**TECHNICAL DATA SHEET**

**Product Description : HS-Ultra Sealer**

HS-Ultra Sealer is a penetrating sealer based on fluoropolymer technology. This formula is especially effective at reducing or preventing the penetration of oils and other stains.

**Benefits:**

- Anti-Dusting properties
- Combats Alkali-Silica-Reaction
- Abrasion Resistant
- Decreases Permeability
- Increases Stain Resistance
- Enhances Surface Gloss
- VOC compliant
- Deep Penetrating Formula
- Increases Coefficient of Friction for safer surfaces

**Use & Application:**

- 1st application 1000 to 2500, depending on refinement and porosity
- 2nd application 2000 to 3500, depending on refinement and porosity

**Before Application:**

It always recommended installers have been through basic training to understand how to measure results in order to proceed through system installations. Many specifications and warranties require the use of certified personnel to assure quality installation.

**Product Specification**

Application:	Sprayer & Microfiber
Appearance:	Odorless, white liquid
VOC:	0 g/L
Shelf life:	1 year after opening
Solvent:	Water based

**Packaging Specification**

Product #	Shipping Wt.	Container
4-FPS-1	10 lbs	1 GAL
4-FPS-5	45 lbs	5 GAL
4-FPS-55	490 lbs	55 GAL
4-FPS-275	2,200 lbs	275 GAL



**Heavy Application:**

1. Surface should be clean and free of any contaminants that prevent water absorption into the surface.
2. Using a sprayer, apply a fine mist to the surface, and immediately work in with a pre-wetted microfiber pad. (soak pad with clean water, then wring out)
3. Continue application, spreading as thin as possible, and keeping a wet edge.
4. Allow sealer to dry.
5. Burnish sealer with hogs hair pad or similar for maximum sealer performance. It is not recommended to use diamond impregnated pads for initial sealer burnishing.
6. For added protection, repeat the process above for a second coat.

**Storage & Shelf Life:**

Should be kept in the original container, with the lid fastened tightly. Store in a cool, dry place raised off the floor. Keep in a temperature range of 40–100°F or 4–38°C and DO NOT allow FREEZE. Seal container again after each use. Keep out of reach of children. Do not mix with other chemicals.

**Cleanup:**

Any solution that cannot be reclaimed and reused should be cleaned with water and disposed of according to local, state and federal regulations.

**Physical Properties:**

<b>Appearance</b>	Odorless clear liquid
<b>VOC Content</b>	0 g/l – free
<b>Freeze point</b>	32°F - 0°C

**VOC Compliance:**

VOC compliant with national, state and district regulations at 0 g/L.

**WARNING & SAFETY INFORMATION:**

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE SAFETY DATA SHEET IN ITS ENTIRETY! Safety Data Sheets (SDS) can be provided by calling 833-585-ADEO (2336).

**WARRANTY INFORMATION:**

The information contained herein is believed to be reliable. This information is based on laboratory testing and results. Because of variations in methods, conditions and equipment, each user must test this product to make a judgment of performance. Applicator is responsible for testing material for effectiveness and performance. Manufacturer obligation is limited to the refund of purchase price or replacement of material if proven to be defective. Claims must be made in writing and received within one year from date of product sale to original buyer.